

## ON-PREMISES LAUNDRY

### Tumble Dryers and Stack Tumble Dryers

25 lb Tumble Dryer  
30 lb Tumble Dryer  
35 lb Tumble Dryer

55 lb Tumble Dryer  
30 lb Stack Tumble Dryer  
45 lb Stack Tumble Dryer

 **Speed Queen.**



# THE BEST IN CLASS JUST GOT BETTER.

100 years. It's a long time for any company to be at the forefront of an industry. And you'd think that a company that's been able to lead for that long must have a finely honed craft — a premier product. Well, you'd be right. For more than a century, Speed Queen has built a legacy on providing equipment that stands up to any commercial laundry challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. Our commitment to quality is only matched by our commitment to your success. The result? The most profitable machines in the industry — bar none.



Some of our competitors may think that a residential machine wrapped in a rugged exterior passes for commercial grade. We believe that strength comes from within. Speed Queen machines are built specifically for the commercial environment. We use metal where others use plastic. Our world-class Test Lab rigorously pushes our products far beyond the conditions they'll face in the field. We believe in being there when our customers need us most. And we go the extra mile at every point of our manufacturing process to ensure that our machines reflect that belief.

For commercial laundry equipment designed for use in fire departments, health care facilities, hotels, correctional facilities, spas, salons, athletics organizations or another industry application, you can rely on the proven performance of Speed Queen to make your life simpler and more productive.

Made in America and refined for more than a century, Speed Queen Laundry equipment represents a secure investment for your on-premises laundry facility.

# DEDICATED TO A HIGHER STANDARD

Uncomplicated. Uncompromising. Unmatched. Enjoy heavy-duty construction that will provide reliable operation for years to come.

Our single pocket tumble dryers feature a concentrated airflow pattern and sealed cylinder rims to ensure maximum air utilization and energy savings. This superior drying performance helps laundries maximize throughput to meet the daily workload without the need for added shifts or costly overtime. Our tumble dryers are designed with fewer moving parts, so that you'll face fewer maintenance problems and less wear and tear. We make it even easier with a large, easy-to-clean lint compartment and a heavy-duty door hinge designed to withstand heavy usage.

## FASTEST MOST EFFICIENT DRYING PROCESS

Axial air flow pattern ensures maximum air utilization for labor and energy savings.

## UNMATCHED RELIABILITY

Quality construction for reliable performance that is backed with a 3-year warranty.

## EASY MAINTENANCE

Large, easy to clean lint compartment simplifies clean-up



## OVER-DRY PREVENTION TECHNOLOGY (OPT)

Reduce linen, labor and utility costs with the precise drying performance of OPT.

## REVERSING CYLINDER OPTION SINGLE AND STACK

Ensures even drying and prevents tangling for easy removal of loads.

### QUANTUM™ GOLD



Quantum™ Gold offers three modes of operation (time, auto and moisture dry) along with the flexibility of 30 programmable cycles and optional moisture sensing technology (OPT) that prevents over drying, saving time and energy.

### DUAL DIGITAL



Set drying time, temperature and cool down. Features include one touch cycle repeat, automatic extended tumble and large digital countdown display.

# ON PREMISES TUMBLE DRYER SPECIFICATIONS

	ST025	ST030	ST035	ST055	STT30	STT45	
<b>Control Option</b>	Quantum Gold, Dual Digital	Quantum Gold, Dual Digital	Quantum Gold, Dual Digital	Quantum Gold, Dual Digital	Quantum Gold, Dual Digital	Quantum Gold, Dual Digital	
<b>Capacity - lb (kg)</b>	25 (11)	30 (14)	35 (16)	55 (25)	30 (14)	45 (20)	
<b>Overall Width - in (mm)</b>	27.9 (710)	27.9 (710)	31.5 (800)	34.5 (876)	31.5 (800)	34.5 (875)	
<b>Overall Depth - in (mm)</b>	39.4 (1000)	45.5 (1155)	45.5 (1155)	53.1 (1350)	42.8 (1090)	48.6 (1235)	
<b>Overall Height - in (mm)</b>	63.9 (1625)	63.9 (1625)	63.9 (1625)	66.7 (1700)	76.3 (1940)	81.3 (2065)	
<b>Cylinder Diameter - in (mm)</b>	26.5 (673)	26.5 (673)	30 (762)	33 (838)	30 (762)	33 (838)	
<b>Cylinder Depth - in (mm)</b>	24 (610)	30 (762)	30 (762)	35 (889)	26 (660)	30 (762)	
<b>Cylinder Volume - cu. ft (liters)</b>	7.7 (220)	9.6 (270)	12.3 (350)	17.3 (490)	10.6 (300)	14.8 (420)	
<b>Reversing Cylinder</b>	Option	Option	Option	Option	Option	Option	
<b>Door Opening Size - in (mm)</b>	22.7 (576)	22.7 (576)	22.7 (576)	26.9 (683)	22.6 (575)	22.9 (581)	
<b>Energy Data</b>	Gas Models - Per Pocket	64,000 Btu/hr	73,000 Btu/hr	90,000 Btu/hr	112,000 Btu/hr	73,000 x 2 Btu/hr	95,000 x 2 Btu/hr
	Steam Models - Per Pocket	83,500 Btu/hr	83,500 Btu/hr	103,400 Btu/hr	-	85,400 x 2 Btu/hr	-
	Electric Models	12kW	21kW	24kW	27kW	21 x 2 kW	-
<b>Gas Connections - in (npt)</b>	0.5	0.5	0.5	0.5	0.5	0.5	
<b>Plumbing Connections - in (npt)</b>	0.75	0.75	0.75	-	0.75	-	
<b>Air Outlet - in (mm)</b>	6 (152)	6 (152)	8 (200)	8 (200)	1 x 8 (200)	1 x 10 (250)	
<b>Motor - HP</b>	Fan	0.5	0.5	0.5	0.5	0.5	2 x 0.5
	Cylinder	0.3	0.3	0.3	0.5	0.3	-
<b>Airflow - cfm</b>	500	500	600	700	2 x 400	2 x 600	
<b>Electrical Specs - amps</b>							
Gas & Steam							
<b>B</b>	100-120V/50/60/1	10	10	10	12	16	-
<b>X</b>	200-240V/50/60/1/3	6	6	6	7	9	12
<b>N</b>	440-480V/50/60/3	3	3	3	3	6	6
<b>P</b>	380-415V/50/60/3	3	3	3	3	6	6
Electric							
<b>D</b>	200-208V/50/60/1	60	104	118	133	-	-
<b>E</b>	230-240V/50/60/1	53	90	102	116	-	-
<b>F</b>	200-208V/50/60/3	36	61	69	78	61 x 2	-
<b>G</b>	230-240V/50/60/3	32	52	59	67	52 x 2	-
<b>H</b>	380V/50/60/3	19	33	37	42	33 x 2	-
<b>J</b>	400-415V/50/60/3	18	30	34	39	30 x 2	-
<b>K</b>	440V/50/60/3	17	29	32	37	29 x 2	-
<b>L</b>	460-480V/50/60/3	15	27	30	34	27 x 2	-
<b>Shipping Dimensions Approx. - in (mm)</b>	Width	30 (760)	30 (760)	33 (840)	35.5 (900)	32.5 (830)	35.5 (900)
	Depth	43 (1090)	49 (1240)	49 (1240)	57 (1450)	47 (1190)	54 (1370)
	Height	67.6 (1720)	67.6 (1720)	67.6 (1720)	70.5 (1790)	79.9 (2030)	84.9 (2160)
<b>Net Weight - lb (kg)</b>	Gas & Steam	300 (135)	320 (145)	340 (155)	430 (195)	570 (260) / 610 (275)	710 (320)
	Electric	310 (140)	330 (150)	350 (160)	440 (200)	660 (300)	-
<b>Shipping Weight - lb (kg)</b>	Gas & Steam	310 (140)	320 (155)	360 (165)	470 (215)	600 (270) / 640 (290)	750 (340)
	Electric	330 (150)	350 (160)	370 (170)	480 (220)	690 (313)	-
<b>Agency Approvals</b>	CSA	CSA	CSA	CSA	CSA	CSA	

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.



by Alliance Laundry Systems

speedqueencommercial.com

AO18-0038 • ©2018 Alliance Laundry Systems LLC